

Specification

The full range consists of ready-made sections of steel wire from 1 to 10 meters with 4S device with a safe working load (SWL):

25 kg


55 kg

85 kg

115 kg

Applications

- Cable trays
- Ducts and ventilation pipes
- Channels and lighting tracks
- Lamps
- Heat radiators



Type	Length m	SWL kg	Pack pcs
NG15-1M	1	25	10
NG15-2M	2	25	10
NG15-3M	3	25	10
NG15-4M	4	25	10
NG15-5M	5	25	10
NG15-6M	6	25	10
NG15-7M	7	25	10
NG15-8M	8	25	10
NG15-9M	9	25	10
NG15-10M	10	25	10
NG20-1M	1	55	10
NG20-2M	2	55	10
NG20-3M	3	55	10
NG20-4M	4	55	10
NG20-5M	5	55	10
NG20-6M	6	55	10
NG20-7M	7	55	10
NG20-8M	8	55	10
NG20-9M	9	55	10
NG20-10M	10	55	10
NG25-1M	1	85	10
NG25-2M	2	85	10
NG25-3M	3	85	10
NG25-4M	4	85	10
NG25-5M	5	85	10
NG25-10M	10	85	10
NG30-1M	1	115	10
NG30-2M	2	115	10
NG30-3M	3	115	10
NG30-4M	4	115	10
NG30-5M	5	115	10
NG30-10M	10	115	10

Other lengths also available upon request.

Available endings



Standard **4S** loop device.
Universal.



Stopper or loop type **KL**
device. Multifunctional.



STL 8x20 pass-through
device. M8 thread.



KV100 pass-through device.
Reversible.

Depending on the needs, we can choose various types of devices, differing in functionality and load capacity. What they have in common is quick assembly and smooth adjustment. All this makes the wires give us unlimited possibilities of attaching any suspension elements. If you do not know which one to choose, contact us, we will help you choose the optimal solution.