



Quick wire suspensions, accessories

Steel wire rope, system, stranded (7x7)/(7x19)



Type	Length m	SWL kg	Min. pack roll
WRA15-100 (7x7)	200	25	1
WRA20-100 (7x7)	100	55	1
WRA25-100 (7x7)	100	85	1
WRA30-100 (7x7)	100	115	1
WRA60-100 (7x19)	100	500	1

Steel wire rope in a reel for creating wire suspensions with corresponding locking clamps.

Locking clamp with quick adjustment, 4Sprint



Type	For wire	SWL kg	Min. pack pcs
4S15	WRA15	15	10
4S20	WRA20	55	10
4S30	WRA30	115	10

Locking clamp for quick and easy suspension of components.
For WRA25 wire, use clamp 4S30. Set with SWL of 85 kg.

Locking clamp with quick adjustment, Rize



Type	For wire	SWL kg	Min. pack pcs
KL100	WRA20	50	10
KL150	WRA30	120	10
KL600	WRA60	500	10

Locking clamp for quick and easy suspension of components.

Universal device lock, two washers and nut



Type	Thread	SWL kg	Min. pack pcs
STL8x20	M8	55	10
STL8x20-D3	M8	110	10
STL10x20	M10	110	10

Universal clamp with thread for creating wire suspensions. Central cable outlet. Recommended torque for tightening the lock nut is 8 nm.

The load capacity of the clamp depends on the type of ARSTE wire used. The specified safe working load (SWL) values are shown in the table opposite.

For wire	SWL kg
WRA15	25
WRA20	55
WRA25	85
WRA30	110

Universal device lock, with square washer and sliding nut



Type	Thread	SWL kg	Min. pack pcs
STL8x20-R	M8	55	10
STL8x20-D3R	M8	110	10

Universal clamp with thread for creating wire suspensions. Central cable outlet. Recommended torque for tightening the lock nut is 8 nm.

The load capacity of the clamp depends on the type of ARSTE wire used. The specified safe working load (SWL) values are shown in the table opposite.

For wire	SWL kg
WRA15	25
WRA20	55
WRA25	85
WRA30	110