

# Quick wire suspensions, accessories



## Universal device lock, with side exit, two washers and nut



Type	Thread	SWL kg	Min. pack pcs
STLS8x20	M8	55	10
STLS8x20-D3	M8	110	10
Universal clamp with thread for creating wire suspensions. Central cable outlet. Recommended torque for tightening the lock nut is 8 nm.			For wire SWL kg
The load capacity of the clamp depends on the type of ARSTE wire used. The specified safe working load (SWL) values are shown in the table opposite.		WRA15	25
		WRA20	55
		WRA25	85
		WRA30	110

## Lighting gripper



Type	Thread	SWL kg	Min. pack pcs
CLM5F	M5	15	10
CLM6F	M6	15	10
Attractive design clip with adjustable wire length, for mounting in lighting brackets. Complete with fixing screw with the thread of your choice.			

## Lighting gripper with hook



Type	SWL kg	Min. pack pcs
CLMHOOK	15	10
Clip with hook and adjustable wire length, for suspending lightweight lamps or other items.		

## Ceiling barrel



Type	Thread	SWL kg	Min. pack pcs
CLB	-	15	10
CLB-M6	M6	15	10
Ceiling bracket with an attractive design, for mounting T/TG type wire suspensions in concrete.			

## Hook for trapezoidal ceiling



Type	SWL kg	Min. pack pcs
TH1	80	10
Sheet metal hook for individual wire suspensions of any length.		

## Carabiner



Type	Dimension mm	SWL kg	Min. pack pcs
K550	5 x 50	100	10
K660	6 x 60	120	10
K770	7 x 70	180	10
K880	8 x 80	230	10

Carabiner for universal applications.