



Quick wire suspensions, accessories

Eye bolt, universal



Type	Thread	Full length mm	Min. pack pcs
SO50-M6/21	M6	50	10
SO80-M6/51	M6	80	10
SO80-M8/40	M8	40	10
SO80-M10/32	M10	80	10
SO120-M10/72	M10	120	10

Bolt with eyelet for universal use.

Eye bolt, industrial



Type	Thread	Full length mm	Min. pack pcs
SOI60-M6/30	M6	30	10
SOI80-M8/40	M8	40	10
SOI100-M10/50	M10	50	10

Bolt with eyelet for universal use.

Catenary wire clamp



Type	Thread	For wire	Min. pack pcs
CGD-M6	M6	max. 3 mm	10
CGD-M8	M8	max. 6 mm	10

Clamp for mounting on a horizontal support line as a substructure for installing wire suspensions. To be used with wire rope type ET/ETG.

Girder support clamp, hammer-in



Type	Opening mm	Flange thickness mm	Min. pack pcs
ZN-4-8	Ø 7	4 - 8	10
ZN-8-14	Ø 7	8 - 14	10
ZN-14-20	Ø 7	14 - 20	10

Support clamp for mounting on I-beams, for suspending wire rope suspensions to steel structures.

Girder support clamp, bolted



Type	Thread	Flange thickness mm	Min. pack pcs
ZNM-8	M8	0 - 18	10
ZNM-10	M10	0 - 20	10

Support clamp for mounting on I-beams, for suspending wire rope suspensions to steel structures.

Wire anchor



Type	Anchor dimension m	Min. pack pcs
KD50	50 x Ø2	10

Easy and quick installation of the wire anchor by inserting and locking into a drilled M8 hole.